2 12:30:44 Flectrical products K-- Technical info version en-HO - Approved

VELUX ACTIVE departure switch KLN 300





VELUX ACTIVE with NETATMO indoor climate control uses sensors to continuously measure temperature, humidity and CO2 levels in your home to ensure a healthier indoor climate. VELUX ACTIVE automatically operates connected VELUX electric products for ventilation and sunscreening when necessary. It also enables control of VELUX electric products using the smartphone app or voice control assistants.

Quickly and easily closes your windows and secures your home.



Technical information

VELUX ACTIVE departure

switch KLN 300

Connection

Wireless connection: the departure switch works with the VELUX ACTIVE gateway

- 300 m free range. It cannot be connected directly to io-homecontro® products.

Departure switch

Materials

Size and weight description

ABS plastic, white (NCS S 1000-N) 80 mm x 80 mm x 10 mm (WxHxD), 0.065 kg.

Installation and use

The departure switch is for indoor use only, between a minimum ambient

temperature 5 °C and a maximum ambient temperature 45 °C. It can be used in a dry or humid environment (such as a hall or an entrance). Radio frequency range: 300 m range open field. Depending on the building

construction, the indoor range is approximately 30 m.

Power consumption

2 x Alkaline AAA (1.5V) batteries Expected battery lifetime: Up to 2 years.